

NAME

sc_prefixscan — scamper driver to test if a set of IPv4 links are point-to-point.

SYNOPSIS

```
sc_prefixscan [ -D] [ -i infile] [ -o outfile] [ -p port] [ -l logfile]
                [ -U unix-socket] [ -w wait] [ -x prefixlen]

sc_prefixscan [ -r data-file] [ -x prefixlen]
```

DESCRIPTION

The **sc_prefixscan** utility provides the ability to connect to a running **scamper(1)** instance and use it to collect data to infer if an IPv4 link is likely a point-to-point link using the **prefixscan** method. An address B is the in-bound interface of a router in a traceroute path if we find an alias A' of the address A returned for the previous hop and A' is a /31 or /30 mate of B, i.e. the link between A and B is a point-to-point link. The **prefixscan** method infers A and A' are aliases if the IPIDs in responses to five alternating probes sent one second apart monotonically increase and differ by no more than 1,000, or probes to A and A' elicit responses with a common source address. The first technique is a pairwise comparison similar to **Ally**, and the second is the **Mercator** technique. The supported options to **sc_prefixscan** are as follows:

- D** causes **sc_prefixscan** to detach and become a daemon.
- i** *infile*
specifies a file containing a list of IPv4 address pairs adjacent in traceroute paths to test if they are point-to-point links.
- o** *outfile*
specifies the name of the output file to be written during the data collection phase. The output file will use the **warts(5)** format.
- p** *port*
specifies the port on the local host where **scamper(1)** is accepting control socket connections.
- l** *logfile*
specifies the name of a file to log progress output from **sc_prefixscan** generated at run time.
- r** *data-file*
specifies the name of the data file to be parsed for point-to-point link inferences that were collected by **sc_prefixscan** in a previous data collection.
- U** *unix-socket*
specifies the name of a unix domain socket where a local **scamper(1)** instance is accepting control socket connections.
- w** *wait*
specifies the length of time in seconds to wait between probing the same IPv4 address with different methods. By default, **sc_prefixscan** waits five seconds between methods.
- x** *prefixlen*
specifies the maximum size of prefix to consider. By default, **sc_prefixscan** considers up to an IPv4 /30 prefix.

EXAMPLES

Given a traceroute with the following path:

```
traceroute to 192.0.30.64
 1 192.0.2.1
 2 192.0.32.10
```

```
3 192.0.31.8
4 192.0.30.64
```

then to collect data to infer if the implied IPv4 links are point-to-point, put the links in a file named `infile.txt` formatted as follows:

```
192.0.2.1 192.0.32.10
192.0.32.10 192.0.31.8
192.0.31.8 192.0.30.64
```

and use a `scamper(1)` daemon listening on port 31337 using:

```
sc_prefixscan -i infile.txt -o outfile.warts -p 31337
```

To obtain the inferred point-to-point links from `outfile.warts`:

```
sc_prefixscan -r outfile.warts
```

SEE ALSO

`scamper(1)`, `sc_ally(1)`, `sc_ipiddump(1)`, `sc_wartsdump(1)`, `sc_warts2text(1)`,
`sc_warts2json(1)`,

M. Luckie and k. claffy, *A Second Look at Detecting Third-party Addresses in Traceroute Traces with the IP Timestamp Option*, Proc. Passive and Active Measurement Conference 2014.

R. Govindan and H. Tangmunarunkit, *Heuristics for Internet Map Discovery*, Proc. IEEE INFOCOM 2000.

N. Spring, R. Mahajan, and D. Wetherall, *Measuring ISP topologies with Rocketfuel*, Proc. ACM SIGCOMM 2002.

AUTHORS

`sc_prefixscan` was written by Matthew Luckie <mjl@luckie.org.nz>.