

NAME

sc_ttlexp — dump source addresses from ICMP TTL expired messages in warts files

SYNOPSIS

```
sc_ttlexp [-O options] [file ...]
```

DESCRIPTION

The **sc_ttlexp** utility provides a dump of source IP addresses contained trace and tracelb records in `warts(5)` files.

The options are as follows:

- ? prints a list of command line options and a synopsis of each.
- O *option*
 - allows the behavior of **sc_ttlexp** to be further tailored. The current choices for this option are:
 - **nodst**: do not dump source address of a TTL expired message if it matches the destination address probed.

EXAMPLES

Given two `warts(5)` files named `file1.warts` and `file2.warts`, the following dumps all source addresses that sent TTL expired messages:

```
sc_ttlexp file1.warts file2.warts
```

Given a compressed warts file named `file3.warts.bz2`, the following dumps all source addresses that sent TTL expired messages, skipping those that were only observed in TTL expired messages from the destination probed:

```
bzcat file3.warts.bz2 | sc_ttlexp -O nodst
```

SEE ALSO

`scamper(1)`, `sc_wartsdump(1)`, `sc_warts2json(1)`,

M. Luckie, *Scamper: a Scalable and Extensible Packet Prober for Active Measurement of the Internet*, Proc. ACM/SIGCOMM Internet Measurement Conference 2010.

AUTHOR

sc_ttlexp was written by Matthew Luckie <mjl@luckie.org.nz>.